

FLUID-setral-SHT 100 K	Nr. 0643
Selected fully synthetic oils with modern EP-additives and anti-oxidants for high temperatures.	Packaging: 20l can 200l drum other packaging on request

Application

For lubrication of chains operation under extreme conditions and temperatures up to +250°C Typical applications: plasterboard dryers, conveyors in the automotive industry, dryers, painting lines, breadmakers.

Characteristics

- NSF H2 registered
- Excellent wear properties
- Excellent corrosion protection
- Outstanding creeping and penetrating properties
- Low friction coefficient
- Adhesive additives prevent dripping and spining-off
- chemical stable
- Silicone-free

Method of use

- According to viscosity application by spray, drip or other central lubrication systems resp. By brush or spray.
- The minimum shelf life in original sealed containers, stored in a cool and dry place (no direct sunlight) is about 2 years.

Technical data

NSF Registration-No.	142349		
Colour	yellow		DIN ISO 2049
Basis	synthetische Ester		
Density, 20°C	0,945	g/cm ³	in house
Viscosity, kinematic at 40°C	≈ 100	mm ² /s	DIN 51562
Flash point, COC	> 250	°C	DIN ISO 2592
Temperature range	- 40 - + 250	°C	

Setral Chemie GmbH
 Salzsteinstrasse 4
 D-82402 Seeshaupt
 Telefon: +49 (0) 88 01 97 10
 Telefax: +49 (0) 88 01 97 30
 Email: info@setral.net

Sétral S.á.r.l.
 13, rue Tannmuhle
 F-67310 Romanswiller
 Téléphone: +33 (0) 3 88 59 11 59
 Télécopie: +33 (0) 3 88 59 11 57
 Email: france@setral.net

The information in this bulletin is, to our knowledge, true and accurate, but all recommendations are without guarantee, since the conditions of use are beyond our control. Setral disclaims any liability incurred in connection with the use of these data or suggestions. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.